



SPO16 CARGO TWO POST LIFTS

16,000 lbs. CAPACITY / SUPER DUTY SYMMETRIC LIFT

SERVICE LONGER VAN WHEELBASES WITH EASE

HEAVY DUTY 3-STAGE ARMS FEATURE A GREATER SPOTTING RANGE FOR SPECIFIC PICKUP POINTS



Minimum / Maximum Arm Reach: 36 13/16" to 74 13/16"
Standard with adjustable thread up adapters



AVAILABLE AS LOW CEILING MODELS
Overall Height: 3' 6" to 14' 6"
Ceiling Height Min: 13' 8" to 14' 8"

MODEL SHOWN:
SPO16U0A0BL
SHOCKWAVE-EQUIPPED

FEATURES:

- 16,000 lbs. capacity
- 2 adjustable lift height options
- 3 column width options
- Rise height of over 75"
- 20 second lowering time
- Available with SHOCKWAVE™ power
- Original "Double S" column
- ALI Gold Certified

SUPERCHARGE SPO16 lifts with SHOCKWAVE™ SPEED

SHOCKWAVE DC powered lifts are the fastest in the world! Accelerate productivity and increase service numbers.



SCAN VIDEO CODE TO LEARN MORE

INCLUDES:

- Thread up adapters for easy vehicle contact
- Set of four (4) clip-on rubber pads for adapters to spot unibody passenger cars
- Four (4) 5" adapter extensions and two (2) 10" adapter extensions for added lifting height and reach



SPO16 CARGO MODELS
BL = Blue / RD = Red

HEAVY DUTY 3-STAGE ARMS
Thread Up Adapters

| STANDARD | SPO16N0A0BL SPO16N0A0RD |
|---|--|
| SHOCKWAVE EQUIPPED | SPO16U0A0BL SPO16U0A0RD |
| Rise* | 77 13/32" - 78 13/32" |
| Overall Height | 15' to 16' 6" |
| Overall Width | NARROW: 12' 11" STANDARD: 13' 5" WIDE: 13' 11" |
| Drive-thru | NARROW: 105 11/32" STANDARD: 111 11/32" WIDE: 117 11/32" |
| Inside Columns | NARROW: 120 15/32" STANDARD: 126 15/32" WIDE: 132 15/32" |
| Front & Rear Arm Min/Max Reach | 36 13/16" - 74 13/16" |
| Min Adapter Height | 5 13/32" |
| Min Adapter Height | 3 3/8" |
| Min Bay Size | 15' x 30' |
| Ceiling Height Min | 15' 2" to 16' 8" |
| Motor / Voltage With SHOCKWAVE | 2 HP, 208-230V 5 HP / 110V |
| Time of Rise / Descent With SHOCKWAVE** | 81 / 20 seconds 60 / 19 seconds |

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke
** Times vary depending on vehicle weight
Heights and widths reflect standard lift model settings

NOTE: Level bay floors provide the best underbody clearance needed to accommodate the broadest range of vehicles to spot and lift. Wide setting installations create the best tire clearance on shorter wheelbases. Vehicle axle weight: MUST NOT EXCEED one half of total lift capability. Maximum arm load is 1/4 of lift rated capacity. SPO16 lifts are designed for most class 4 and 5 vehicles. Some vehicles within each class may exceed arm capacity but not the lift capacity. Please consult vehicle axle information and lift manual for more information.

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com     

North / South America Information

Sales: 800.640.5438
userlink@rotarylif.com

Tech. Support: 800.445.5438
techlink@rotarylif.com

Global Contact Information

USA: 1.812.273.1622
Canada: 1.905.812.9920
Latin America / Caribbean: 1.812.273.1622
Brazil: +55.11.4534.1995

Government Sales: 800.445.5438 X5655

For additional information: rotarylif.com/Government-Purchasing-Assistance/



Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

Lit# Rotary SPO16 CARGO Cutsheet.2020.07

©2020 VEHICLE SERVICE GROUP™. Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.